

The iFolder client checks for updates on the server whenever a user logs in, and prompts the user to install a new update if it exists.

**IMPORTANT:** Ensure that you update the version configuration file with the version number and the filename for the respective client platform. Until the version configuration file is updated, user does not get the upgrade prompt. For more information on editing the version configuration file.

New clients available should be placed on the server in the location  
 {prefix}/%\_lib/simias/web/update/{windows/linux/mac}/<file\_name>

### Updating the Version Configuration Files

`/usr/%_lib/simias/web/update` and open the version configuration file for the respective client.

Platform	Version Configuration File	
Linux	<p><code>unix-version.config</code></p> <p>Each time a Linux iFolder Client authenticates to an iFolder Server, it checks for an updated client on the server. The server uses <code>unix-version.config</code> file to determine whether an upgrade exists for a given linux client. You may specify multiple distribution match tags within this file. The match attribute is compared against the client's <code>/etc/issue</code> file. A contains search is performed in order of the distribution tags listed in the file and the first match is used to upgrade the client. If no matches are found, the DEFAULT distribution is used.</p>	
Windows	<p><code>verion.config</code></p> <p>If the specified version is greater than the iFolder version on the client, the user is prompted to upgrade their ifolder application with the one specified in the <code>version.config</code> file by filename.</p>	
Macintosh	<p><code>mac-version.config</code></p> <p><b>Example :</b></p>	
Platform	Client	Tag to Update (Example)
Linux	SUSE 11.1	<pre>&lt;distribution match="openSUSE"&gt;   &lt;version&gt;3.7.2&lt;/version&gt;   &lt;download-directory&gt;opensuse- linux&lt;/download-directory&gt; &lt;/distribution&gt;</pre>
Windows	<ul style="list-style-type: none"> <li>Windows 32</li> <li>Windows 64 (Vista)</li> </ul>	<pre>&lt;distribution match="windows32"&gt;   &lt;version&gt;3.7.2&lt;/version&gt;   &lt;filename&gt;ifolder3- windows.exe&lt;/filename&gt; &lt;/distribution&gt;</pre>
Mac	Intel Macintosh v10.4	<pre>&lt;version&gt;3.7.2&lt;/version&gt; &lt;filenamme&gt;ifolder3- mac.dmg&lt;/filename&gt;</pre>

To add upgrades for other Linux platforms , add another entry in `unix-version.config` with distribution match having contents of `/etc/issue`.